


Ultra-Thin Fuse | 0.06x0.03"

0603FA-L Series

Fast Acting series Thin Film Chip Fuse

Features:

- Very fast acting at 300% overload current
- Low DCR
- High inrush current withstanding capability
- High reliability
- Fiberglass enforced epoxy fuse body
- Copper termination with nickel and tin plating layer
- Halogen free, RoHS compliance & lead-free



Application:

- Panel
- HDD
- Toy
- IoT
- Battery pack
- Finger print
- Smart lock
- Notebook

Electrical Characteristics


% of Current Rating	Opening Time
100%	4hours min.
300%	5second max.
450%	0.2second max.

Specifications

Part No.	Current Rating(A)	Voltage Rating (Vdc)	Interrupting Rating	Typical Cold DCR (Ω)	Typical I^2t (A^2Sec)*	Marking
0603FA-R500-LYY	0.5	35	35A @35V	0.11	0.02	F

*Typical I^2t : i.e. melting I^2t at 0.001s of current rating

Dimension



Packaging


- Quantity: 5, 000pcs
- 8mm wide tape on 178mm (7 inch) diameter reel -specification EIA Standard 481

Ultra-Thin Fuse | 0.06x0.03''

0603FA-L Series

Fast Acting series Thin Film Chip Fuse

Soldering Parameters



IR Reflow Profile

Preheat

Temperature min (T _{smin})	150°C
Temperature max(T _{smax})	200°C
Time (T _{smin} to T _{smax}) (t _s)	60 – 120 seconds
Average ramp up rate (T _{smax} to T _p)	3°C/second max


Reflow

Liquidous temperature (T _L)	217°C
Time at liquidous (t _L)	60 – 150 seconds
Peak temperature(T _p)	260°C
Time within 5°C of actual peak Temperature (t _p)	30 seconds*
Average ramp-down rate(T _p to T _{smax})	6°C/second max
Time 25 °C to peak temperature	8 minutes Max.

Wave Soldering: 260°C, 10 seconds max.

Infrared Reflow: 260°C, 30 seconds max.

Temperature Effect on Current Rating



- Normal ambient temperature: 23+/-3°C
- Operating temperature: -55 ~ 105°C

Ultra-Thin Fuse | 0.06x0.03''

0603FA-L Series

Fast Acting series Thin Film Chip Fuse

Average Time-Current curve

